
PRO VENTUNO



DATASHEET

ADVANTouch PRO VENTUNO

PCAP-TOUCH

HIGH PRECISION






























The ADVANTouch PRO Ventuno opens a new era in the world of conferencing by enabling virtual collaboration in unprecedented realism through avantgarde innovations. Seamless Android and Windows split-

screen connectivity and multi-window mode in stunning 5K resolution expand the uses of existing applications while significantly increasing efficiency and saving valuable time.

- INNUMEROUS CONNECTIVITY OPTIONS
- **ANDROID 13 OTA-ENABLED**
- **EFFICIENT HIGH-END CPU & GPU**
- **CAPACITIVE TOUCH TECHNOLOGY**
- PRESSURE SENSITIVE TOUCH PENS
- **OPS PC STANDARD**
- 8GB RAM & 64GB EMMC

- ADVANSHARE PRE-INSTALLED
- ✓ PRESENCE & LIGHT SENSOR
- ▲ MODERN & ELEGANT DESIGN
- ▲ NUMEROUS SETTINGS
- ✓ PLACE HAND & RULER WHEN WRITING



ADVANTOUCH PRO Ventuno	
Screen diagonal	105" / 277 cm
Panel type	LCD (D-LED)
Touch surface	2450 x 1034 mm
Aspect ratio	21:9
Resolution & Frequency	5K (5120 x 2160) / 60Hz
Color depth	10-Bit
Brightness (typical / maximum)	400 / 430 cd/m ²
Contrast (dynamic / static)	5000:1 / 1200:1
Response time	6,5 ms
Viewing angle	178°
Glass type & hardness	anti-reflective safety glass / 7 Mohs

COMPUTER	
Operating system	ADVANOS (Android 13)
CPU	Octa-Core
Working memory	8 GB
Internal memory	64 GB
PC module (optional)	ADVANTouch OPS (80 Pin)

INTERACTIVITY	
Touch technology	Projected capacitive (PCAP)
Touch points (Windows / Android)	40 / 32
Writing tools	Finger, active & passive capacitive stylus
Accuracy	± 1,5mm (90% area)
Active pens Pressuresensitivity	4096 levels
Minimum object size (active / passive)	3mm / 8mm



CONNECTIONS	
USB-A	4x 3.0, 3x 2.0
USB-B (Touch)	3x 2.0
USB-C	1x In (PD 65W / DP 1.4 / network)
HDMI (5K60Hz)	4x In (CEC/ARC: HDMI 1), 1x Out
Displayport	1x In
LAN / RJ45	2x In/Out
Audio	1x 3.5mm In, 1x 3.5mm Out, 1x SPDIF (PCM)
Serial	1x RS232
Wi-Fi module (integrated)	SI07B, 802.11a/b/g/n/ax (2.4GHz / 5GHz)
Bluetooth ®	5.0

SENSORS	
Environment	Light, PIR, Temperature and Humidity, CO2/VOCS, PM 2.5

AUDIO - LOUDSPEAKER	
Channels	2.1
Power (loudspeaker / subwoofer)	2 x 16W / 1 x 16W
Sound pressure level	86dB/mW

PHYSICAL DATA	
Dimension (width x height x depth)	2505 x 1132 x 90 mm
Weight (net / gross)	91,2 / TBD* kg
VESA mount	1000 x 400 mm

The determination of the gross weight according to legal guidelines is currently being carried out and will be completed soon.



^{*}TBD (To Be Done):

SCOPE OF DELIVERY	
Pens	2 active pens + charging station, 2 passive pens
Remote control	Yes
Cabel	Power cable 3m, HDMI cable 5m, USB touch cable (A/B) 5m

SERVICE & SUPPORT	
Warranty	Third countries: 12 months bring-in EU countries: 24 months bring-in
Extension	Warranty extension to 5 years (optional)

USE	
Power consumption (standard / standby)	TBD**
Lifetime	50.000 h




**TBD (To Be Done):

Measurements and determinations of electricity consumption according to legal guidelines are currently being carried out and will be completed soon.

SPECIFICATION




View from left




View from right

Front view



View from below

Backview



Presented by

Version: 01.01.2025 Subject to changes, errors and technical developments!

